

# EPDM diaphragms

EPDM and EPDM plus diaphragms

## Features and benefits

- All our diaphragms are laser-etched with cure dates and batch numbers, ensuring that they are completely traceable
- Wide temperature range; good in steam applications
- Not suitable for use with solvents or petroleum agents
- Parylene surface treated version available



## Technical specifications

	EPDM diaphragms
Colour	Black
Diaphragm variant(s)	Bellows, Straight
Parylene treatment	No
Operating temperature range	-51 to 135 °C
Operating temperature range	-60 to 275 °F
	4.83
Max. operating pressure	70 psig
Compatible actuators	AJS, AKS
	300
	3000
Shelf life	5 years
Material specification	Ethylene propylene diene monomer (peroxide cured)
Standards	ASME BPE, RoHS
Certification and compliance	ADCF, BSE/TSE free, FDA 21CFR177.2600, USP <87>

## Materials of construction

	EPDM diaphragms
	RS60065B FDA Grade ethylene propylene diene monomer rubber
Inserts	304 SS

---

Disclaimer: The information contained in this document is believed to be correct but ASEPCO accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the users responsibility to ensure product suitability for use within their application. Radial diaphragm is a trademark of ASEPCO Corporation. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. A member of Watson-Marlow Fluid Technology Group, A Spirax-Sarco Engineering plc company.

*[wmfts.com/global](https://wmfts.com/global)*



01 August 2024