

# Platinum-cured silicone braided hose



Platinum-cured silicone braided hose

## Features and benefits

- Manufactured and packed within an ISO 14644 Class 7 cleanroom
- Post sterilised validation to current USP, EU and FDA standards
- Withstands sterilisation and repeat autoclave
- Available in either 7.6 m (25 ft) and 15.2 m (50 ft) coils



## Technical specifications

	Platinum-cured silicone braided hose
Bore size	3.2 - 25.4 mm
Bore size	0.125 - 1 in
External diameter	8.8 - 34.5 mm
External diameter	0.345 - 1.36 in
Length	7.6 - 15.2 m
Length	25 - 50 Ft
Certification and compliance	ADCF, ISO 10993, ISO Class 7, Ph. Eur. 3.1.9, USP <788>, USP <95>, USP <97>, USP Class VI
Operating temperature range	-65 °C to 254 °C
Operating temperature range	-85 °F to 490 °F
Burst pressure	15.1 - 48.3 bar
Burst pressure	220 - 700 psi
Shelf life	5 years
Gamma stability	Max 50 kGy
Autoclave stability	Yes
Bend radius	25.4 - 101.6 mm
Bend radius	1 - 4 in

## Materials of construction

	Platinum-cured silicone braided hose
Inner tube	Platinum-cured silicone
Braid layer 1	Polyester
Outer tube	Platinum-cured silicone

## Product codes

Part number	I.D. mm (inch)	O.D. mm (inch)	Length m (ft)	Min. bend radius mm (inch)	Min. burst pressure at 20C/68F bar (psi)
BPSHP0125-C	3.2 (0.125)	8.8 (0.345)	7.6 (25)	25.4 (1.00)	48.3 (700)
BPSHP0188-C	4.8 (0.187)	10.3 (0.407)	7.6 (25)	31.8 (1.25)	44.3 (650)
BPSHP0250-C	6.4 (0.250)	12.4 (0.490)	7.6 (25)	38.0 (1.5)	43.1 (625)
BPSHP0375-C	9.6 (0.375)	16.7 (0.658)	7.6 (25)	44.4 (1.75)	37.9 (550)
BPSHP0500-C	12.7 (0.500)	20.3 (0.800)	7.6 (25)	50.8 (2.00)	34.5 (500)
BPSHP0625-C	15.9 (0.625)	24.5 (0.965)	7.6 (25)	63.5 (2.5)	28.9 (420)
BPSHP0750-C	19.0 (0.750)	27.9 (1.100)	7.6 (25)	76.2 (3.00)	24.1 (350)
BPSHP0875-C	22.2 (0.875)	32.0 (1.260)	7.6 (25)	88.9 (3.50)	20.7 (300)
BPSHP1000-C	25.4 (1.00)	34.5 (1.360)	7.6 (25)	101.6 (4.00)	15.1 (220)
BPSHP0125-D	3.2 (0.125)	8.8 (0.345)	15.2 (50)	25.4 (1.00)	48.3 (700)
BPSHP0188-D	4.8 (0.187)	10.3 (0.407)	15.2 (50)	31.8 (1.25)	44.3 (650)
BPSHP0250-D	6.4 (0.250)	12.4 (0.490)	15.2 (50)	38.0 (1.5)	43.1 (625)
BPSHP0375-D	9.6 (0.375)	16.7 (0.658)	15.2 (50)	44.4 (1.75)	37.9 (550)
BPSHP0500-D	12.7 (0.500)	20.3 (0.800)	15.2 (50)	50.8 (2.00)	34.5 (500)
BPSHP0625-D	15.9 (0.625)	24.5 (0.965)	15.2 (50)	63.5 (2.5)	28.9 (420)
BPSHP0750-D	19.0 (0.750)	27.9 (1.100)	15.2 (50)	76.2 (3.00)	24.1 (350)
BPSHP0875-D	22.2 (0.875)	32.0 (1.260)	15.2 (50)	88.9 (3.50)	20.7 (300)
BPSHP1000-D	25.4 (1.00)	34.5 (1.360)	15.2 (50)	101.6 (4.00)	15.1 (220)

Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the user's responsibility to ensure product suitability for use within their application. Watson-Marlow and WMArchitect are registered trademarks of Watson-Marlow Limited. BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve and BioTube applicator are Trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. Q-Clamp is used under licence.

[wmfts.com/global](http://wmfts.com/global)



05 July 2024