

# PF22/QC22

PF22 peristaltic filling machine


## Features and benefits

- Fill volumes from 0.17 fl oz (5 ml) to more than 169.07 fl oz (5000 ml) with  $\pm 0.5\%$  accuracy
- Changing the fluid path can be achieved in less than one minute
- Consistent filling accuracy prevents costly overfilling
- No foaming, splashing or dripping between fills
- No cross-contamination



## PF22/QC22 performance

PF22 – capacity diagram (based on water)




## Technical specifications

	PF22/QC22
Filling volume range	5-5000 ml
Accuracy	±0.5 %
Ingress Protection	IP31
Power supply	110/230 VAC, 50/60 Hz
Power consumption	Max 350 W
Weight	25 kg
Weight	55 lbs
Accessories	Filling nozzles, tubes, filling stand, pneumatic diving nozzle system, foot switch, printer
Compatible tubing size	3.0 to 12.5 mm ID

## Materials of construction

	PF22/QC22
Casework	Anodized aluminum, Stainless steel AISI 304
Pumphead body assembly	Anodized aluminum
Pumphead roller assembly	Anodized aluminum, Stainless steel 304

## PF22/QC22 dimensions



*Dimensions in mm/inch*

---

Disclaimer: The information in this document is believed to be correct, but Watson-Marlow Flexicon A/S accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. WARNING: These products are not designed for use in, and should not be used for, patient-connected applications. WMArchitect and Accusil are registered trademarks.

*[wmfts.com/global](https://wmfts.com/global)*



05 July 2024